


VOLVO POWER VE D12 435



SPECIFICATIONS

Model	Volvo VE D12 435 for VHD only
Base Engine Configuration	4 cycle / inline 6 Aspiration / intercooler Turbocharged / air to air Cam / valve configuration SOHC / 4 per cylinder Cylinder head One Piece Injection system Electronic Unit Injectors (EUI) Electronic management system VECTRO III Horsepower Derating (365, 395) software Displacement, cu in (L) 740 (12.13) Compression ratio 17.3:1 Bore & stroke, in (mm) 5.16 x 5.90 (131 X 150) Dry weight, lb (kg) 2477 (1126)
Engine Ratings, hp	435 435 @ 1800 / 1550 @ 1200 2100 (2300) Recommended cruise range, rpm 1400 - 1650 Start engagement torque lb ft 627 @ 800
Oil Service Intervals, etc.⁽¹⁾	Total oil change capacity, in qts (L) 39 (37) Number of oil filters 2 full flow, 1 by-pass Oil change: Severe duty, VDS-2 or EO-N Prem Plus oil 12,000 miles / 19,000 km / 300 h Standard duty, VDS-2 or EO-N Prem Plus oil 15,000 miles / 24,000 km / 400 h Extended oil drain, VDS-2 or 25,000 miles / 40,000 km / 600 h EO-N Prem Plus oil only
Engine Equipment	Compressor (CFM) 18.7 Exhaust pressure governor (EPG) Standard EPG, Exhaust brake rating 225 hp @ 2300 Preheater Available Engine compression brake Available VEB, Compression brake rating 350 hp @ 2300 Engine brake weight, lb (kg) 25 (12) Side engine PTO Available, 60 hp / 370 lb ft Front engine PTO Available, 180 hp / 500 lb ft
Base Warranty⁽²⁾	Major components 24 months / 250,000 miles / 6,250 hours Emission components 60 months / 500,000 miles / 12,500 hours 100% parts & labor 60 months / 250,000 miles / 6,250 hours
Extended Warranty⁽²⁾	Various parts & labor plans available 60 months / 500,000 miles / 12,500 hours



VOLVO


New Roads

(1) For complete information see TSI 175.001.


(2) Conditions and limitations apply. See dealer for details.

VOLVO POWER VE D12 435


VE 435



RETARDING POWER



VOLVO DRIVETRAIN RECOMMENDATIONS



GVW / GCW in lb x 1000	75 - 105	95 - 140
Truck configuration	6 X 4	
Engine type	VE 435 for VHD only	
Recommended cruise range, rpm	1500 - 1600	1550 - 1650
Governed rpm @	2100	
Manual transmissions^(1,2)	0.73 overdrive	0.73 overdrive
Tire sizes (revs / mile)	478 - 516	
Rear axle ratios	3.70 - 4.30	3.70 - 4.30
Recommended cruise speed (mph)	63 - 68	53 - 68
Top speed range (mph)	66 - 78	58 - 78
Minimum startability	20%	

(1) A gradeability below 1% at "cruise speed" will result in poor driveability.

(2) When operating in hilly terrain and GCW exceeds 90,000 lbs., a "13-, 15- or 18-speed" transmission is recommended.

VOLVO

Volvo Trucks North America, Inc.

P.O. Box 26115, Greensboro, NC 27402-6115

Volvo Trucks Canada, Inc.

5600A Cancross Court, Mississauga, Ontario L5R 3E9

www.volvotrucks.us.com

Information in this brochure is current at time of printing. Specifications subject to change. ©Volvo Trucks North America, Inc., 2002. All rights reserved.

PV835-669